



Technical Datasheet

DL-44 Degreaser Label-remover

Description

DL-44 is an efficient industrial cleaner which dissolves grease, oil, dirt, soot, printing ink, Indian ink, most non-hardened adhesives and glue remnants.

DL-44 does not contain any corrosives, is gentle and pH-neutral, which makes it safe on both glass, metal, laminate, bricks, painted surfaces, rubber and wood.

After about 5 minutes the most normal-drying adhesives (non-hardened types) are neutralized and label- or glue remnants can be removed.

DL-44 contains ingredients meeting USDA K3.

Properties

- label remover
- efficient degreaser
- reliable and gentle
- pH-neutral
- based on citrus oil
- wide application area
- removes dirt, grease, oil etc.



Application

Apply DL-44 on the label or the subject, which has to be removed. Let it soak in a few minutes to ensure a complete penetration, so that the active citrus oils can neutralize the bond strength in the glue remnants.

Remove the applied subject and wipe the surface with a clean cloth/towel. If necessary rinse with water or wipe the surface with a moist cloth/towel.

Note! It is recommended always to make a test on small areas before use, as DL-44 can influence certain types of plastics and a few special lacquers.

ITW Chemical Products Scandinavia

Priorsvej 36 • DK-8600 Silkeborg • Phone: +45 86 82 64 44 • Fax: +45 86 82 64 64 • e-mail: info@itw-scan.dk • www.itw-scan.dk

Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.

Date: 15.01.2004

INFORMATION

DL-44 Degreaser

Technical and physical data

Partnumber	01175	26050
Packing	500 ml spray	50 ml spray
Contents	500 ml	50 ml
Weight	375 g	37 g
Propellant	CO ₂	
Base	citrus oil	
Appearance	clear/transparent	
pH	neutral	
Density	0,833 g/ccm	0,74 g/ccm
Odour	citrus	
Flashpoint	46°C	
Emptying rate	0,37 g/sec	0,76 g/sec

Information

For more technical information and Material Safety Datasheets for the products at ITW, please contact:

***ITW* Chemical Products Scandinavia**

*Priorsvej 36
DK-8600 Silkeborg
Phone: +45 86 82 64 44
Fax: +45 86 82 64 64
e-mail: info@itw-scan.dk
www.itw-scan.dk*