



## Technical Datasheet

---

# GL-68 Slideway Lubricant

### Description

Special lubricant for the protection and lubrication of machine tools. Reduces the friction, and the "stick-slip" effect is completely avoided and the maximum precision of the machine is achieved.

The oil is very suitable for the lubrication of slideways, but can also be used for gears on machine tools. This means that often the machine can be maintained with just this one oil.

GL-68 can be used as lubricant for chains and machines, which require drip-free lubrication. An all-round oil-spray for many different applications.

The base oil in GL-68 meets the new specifications P47 and P50 from Cincinnati.

### Properties

- prevents the "stick-slip" effect
- gives slideways a long life
- drip-free lubrication
- for machine tools
- non-drying
- strong adhesive
- all-round



**ITW Chemical Products Scandinavia**

Priorsvej 36 • DK-8600 Silkeborg • Phone: +45 86 82 64 44 • Fax: +45 86 82 64 64 • e-mail: [info@itw-scan.dk](mailto:info@itw-scan.dk) • [www.itw-scan.dk](http://www.itw-scan.dk)

*Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.*

Date: 01.10.2007

INFORMATION

# GL-68 Slideway Lubricant

## Technical and physical data

|  |                         |
|--|-------------------------|
| Partnumber   | 22025                   |
| Packing  | Spray                   |
| Contents   | 500 ml                  |
| Weight   | 356 g                   |
| Propellant   | Propan/Butan            |
| Base   | Mineral oil             |
| Colour   | Colourless/transparent  |
| Flashpoint (conc.)                                     | >200°C                  |
| Density at 20°C  | 0,714 g/cm <sup>3</sup> |
| Solubility in water                                    | Insoluble               |
| Meets the requirements according to the RoHS directive | YES                     |

## Information

For more technical information and Material Safety Datasheets for the products at ITW, please contact:

### ***ITW*** Chemical Products Scandinavia

*Priorsvej 36*

*DK-8600 Silkeborg*

*Phone: +45 86 82 64 44*

*Fax: +45 86 82 64 64*

*e-mail: [info@itw-scan.dk](mailto:info@itw-scan.dk)*

*[www.itw-scan.dk](http://www.itw-scan.dk)*