



Technical Datasheet

GM-12 Sliding Agent

Description

GM-12 is especially designed for the mounting of electric cables and rubber strips etc. It gives easy mounting and the seizing is avoided.

The sliding agent removes the friction in the process of the assembling of drain pipes, soil pipes and pressure pipes made of PVC-plastic and at the same time it is gentle to tube packings etc.

GM-12 is also suitable as vinyl make-up for cars. Apply a thin layer and polish with a dry cloth.

Properties

- 36% silicone
- for PVC-pipes, electric-cables, rubber strips etc.
- easy mounting
- prevents seizing of PVC and rubberparts
- effektive from -50°C to +200°C
- prevents static electricity and corrosion
- for movable and stationary parts
- antiadhesive surface
- colourless



Also available in 5, 25 and 200 litres

ITW Chemical Products Scandinavia

Priorsvej 36 • DK-8600 Silkeborg • Phone: +45 86 82 64 44 • Fax: +45 86 82 64 64 • e-mail: info@itw-scan.dk • www.itw-scan.dk

Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.

Date: 27.01.2004

INFORMATION

GM-12 Sliding Agent

Technical and physical data

Partnumber	07395	
Packing	spraycan	
Contents	500 ml	
Weight	322 g	
Propellant	propane/butane	
Base	silicone	
Viscosity at 25°C	1000 cSt	CTM 0004
Flashpoint open cup	over 321°C	CTM 0006
Dropping point	-50°C	CTM 0133
Density at 25°C/15.6°C	0.664 g/cm ³	CTM 0001A
Temperature resistance	0.61	CTM 0747
Emptying rate	1,172 g/sec.	
Product Registration number	1028591	

Information

For more technical information and Material Safety Datasheets for the products at ITW, please contact:

***ITW* Chemical Products Scandinavia**

*Priorsvej 36
DK-8600 Silkeborg
Phone: +45 86 82 64 44
Fax: +45 86 82 64 64
e-mail: info@itw-scan.dk
www.itw-scan.dk*