



## Technical Datasheet

# KK-2002 Chainoil Clear

### Description

KK-2002 is a lubricant designed for the maintenance of chains and cables in the food industry where a non-smudging heavy-duty lubrication is needed. The extreme capability of adhesion and temperature resistance results in long lubrication intervals and reduces wear and corrosion under moisture conditions. Quick spread of the oil ensures a very effective penetration and a viscous water-repellent lubrication.

KK-2002 is a high performance lubricant with an excellent capability of adhesion and lubricity for use in very difficult situations. The capability of adhesion resists the centrifugal force from fast running chains, both under wet and dry conditions and also during heavy load. The temperature ranges  $-30^{\circ}\text{C}$  to  $+180^{\circ}\text{C}$ , briefly up to  $+200^{\circ}\text{C}$ .

KK-2002 is suitable for trucks, transmissions, bolts, assemblies, hinges, conveyors, chains, bearings, axles, shells, elevator wires, certain open gear, toothed wheels, chain-saws etc.

KK-2002 comply with the demands of USDA H2

### Product advantages

- non-drip
- reduces lubrication intervals and wear
- very adhesive and viscous
- effective from  $-30^{\circ}\text{C}$  to  $+180^{\circ}\text{C}$
- optimum lubricant characteristics
- sound-absorbing
- water-repellent - also against sea water
- rust preventing



Also available in 5, 25 and 200 litres

**ITW Chemical Products Scandinavia**

Priorsvej 36 • 8600 Silkeborg • Phone: +45 86 82 64 44 • Fax: +45 86 82 64 64 • e-mail: [info@itw-scan.com](mailto:info@itw-scan.com) • [www.itw-scan.com](http://www.itw-scan.com)

*Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.*

Date: 15.01.2004

INFORMATION

# KK-2002 Chainoil Clear

## Technical and physical data

Item no.	11845	
Packing	spraycan	
Contents	500 ml	
Weight	375 g	
Propellant	propane/butane	
Base	mineral/synthetic	
Apperance	penetrating foam	
Additives	corrosion, EP, adhesive and antiwear	
Flashpoint	240°C	
Floatpoint	-3°C	
Viscosity at 40°C	960 cSt	ASTM-D445
Cu-Strip	test 1 a	
ISO-VG	220	
Colour	transparent/light yellow	
Density	0,758 g/cm <sup>3</sup>	
Emptying rate	0,916 g/sec	

## Information

For futher technical information and Material Safety Data Sheet for the ITW products, please contact:

***ITW* Chemical Products Scandinavia**

*Priorsvej 36*

*8600 Silkeborg*

*Tlf.: 86 82 64 44*

*Fax: 86 82 64 64*

*e-mail: [info@itw-scan.com](mailto:info@itw-scan.com)*

*[www.itw-scan.com](http://www.itw-scan.com)*